

SA15RA

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3500	345 / 0.40	438 / 0.60	541 / 0.78	628 / 0.97	707 / 1.18	781 / 1.41	850 / 1.66	916 / 1.92	979 / 2.20
4000	394 / 0.60	471 / 0.83	566 / 1.04	649 / 1.24	724 / 1.46	793 / 1.70	859 / 1.96	921 / 2.23	981 / 2.52
4500	444 / 0.85	508 / 1.12	593 / 1.36	672 / 1.59	744 / 1.82	810 / 2.06	872 / 2.33	932 / 2.61	989 / 2.91
5000	493 / 1.17	548 / 1.47	622 / 1.75	698 / 2.00	767 / 2.25	831 / 2.51	890 / 2.78	947 / 3.07	1001 / 3.38
5500	542 / 1.56	590 / 1.88	655 / 2.20	725 / 2.49	792 / 2.76	853 / 3.04	911 / 3.32	965 / 3.62	1018 / 3.93
6000	592 / 2.02	634 / 2.38	691 / 2.73	755 / 3.06	818 / 3.36	878 / 3.66	934 / 3.96	987 / 4.27	1037 / 4.59

Max Sizeable RPM = 1100 RPM. Table shown extended beyond this point for reference only.