

**SA18RA**

CFM	Static Pressure in Inches W.G.										
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
6500	343 / 1.04	415 / 1.32	477 / 1.65	539 / 2.00	601 / 2.33	660 / 2.65	716 / 2.97	770 / 3.29	821 / 3.62	869 / 3.97	915 / 4.33
7000	370 / 1.30	437 / 1.59	496 / 1.95	553 / 2.32	611 / 2.68	667 / 3.03	721 / 3.38	773 / 3.72	823 / 4.07	871 / 4.43	916 / 4.79
7500	396 / 1.60	460 / 1.90	515 / 2.28	569 / 2.67	623 / 3.07	676 / 3.45	728 / 3.82	778 / 4.19	827 / 4.56	874 / 4.94	919 / 5.32
8000	422 / 1.95	483 / 2.25	535 / 2.65	586 / 3.07	636 / 3.49	687 / 3.91	736 / 4.31	785 / 4.71	832 / 5.10	877 / 5.50	922 / 5.89

Max Sizeable RPM = 1200 RPM. Table shown extended beyond this point for reference only.