

SA920RA

CFM	Static Pressure in Inches W.G.												
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
10000	382 / 2.18	435 / 2.65	486 / 3.07	532 / 3.49	576 / 3.92	618 / 4.37	658 / 4.85	699 / 5.36	738 / 5.91	777 / 6.48	816 / 7.08	854 / 7.70	891 / 8.34
11000	420 / 2.90	469 / 3.42	516 / 3.89	559 / 4.35	600 / 4.81	639 / 5.29	677 / 5.79	715 / 6.32	751 / 6.87	788 / 7.45	823 / 8.06	859 / 8.69	894 / 9.35
12000	458 / 3.77	503 / 4.34	547 / 4.86	588 / 5.37	627 / 5.87	664 / 6.37	699 / 6.90	734 / 7.44	768 / 8.01	802 / 8.60	836 / 9.22	869 / 9.86	
13000	496 / 4.79	537 / 5.41	579 / 5.99	618 / 6.54	654 / 7.08	689 / 7.62	723 / 8.17	756 / 8.74	789 / 9.33	820 / 9.94			
14000	534 / 5.98	573 / 6.65	610 / 7.27	648 / 7.89	683 / 8.47	717 / 9.05	749 / 9.64						
15000	572 / 7.36	608 / 8.08	644 / 8.76	679 / 9.42									

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.