


MODULAR OUTDOOR DOWN DISCHARGE ELECTRIC HEATER-ROOF TOP PACKAGE WITH COOLING COIL, V-BANK AND INTAKE HOOD

IHVBSHACCRRTP  
REV#2 6/1/2009



ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHES.

EXHAUST UNIT DIMENSIONS			
MODEL #	T	U	V *
BDU1	14-1/2	22	19
BDU2	18-1/2	27-1/4	21
BDU3	21-1/2	30-1/4	21
BDU4	23	33-3/4	24-3/4
BDU5	23-1/2	39-3/8	28
BDU6	29-1/2	36-7/8	28
BDU7	30-5/8	43-3/8	33
BDU8	33-1/2	52-3/4	40

MODEL	WEIGHT	UNIT DIMENSIONS													CURB/RAIL		DISCHARGE OPENING		
		A	B	C	D	E	F	J	K	L	M	N	P	R	S	T	U	V *	
E1-G10	1080 LBS	167-1/4	39-3/8	42-3/4	39	3-3/4	44-3/8	21	71	106	166-5/8	3-9/16	13-7/8	36-13/16	11-1/2				
E2-G15	1485 LBS	181-1/4	49-3/8	47-3/4	44	3-3/4	53-3/8	31	79	124	190-5/8	4-5/16	22-3/8	46-9/16	18				
E3-G18	1785 LBS	192-1/4	54-3/8	56-3/8	51-1/8	5-1/4	51-5/8	35	84	133	199-5/8	6-5/16	22-3/8	49-1/2	18				
E4-920	2860 LBS	238-9/16	60-7/16	64-3/8	59-1/8	5-1/4	76-3/8	42	115-3/16	171-3/16	255-7/8	5-1/4	31-1/2	56-13/16	23-1/2				

MODEL	MIN.	MAX.	FILTER SIZE & QTY.		MAX. FILTER VELOCITY
			MIN.	MAX.	
E1-G10	3 Ton	12.5 Ton	20"x25"x2" (3)	20"x25"x2" (3)	63600 CFM = 418 FPM
E2-G15	5 Ton	20 Ton	16"x20"x2" (8)	16"x20"x2" (8)	65000 CFM = 464 FPM
E3-G18	10 Ton	25 Ton	20"x25"x2" (8)	20"x25"x2" (8)	68000 CFM = 348 FPM
E4-920	20 Ton	40 Ton	16"x20"x2" (15)	16"x20"x2" (15)	81300 CFM = 495 FPM

ROOF OPENING 2" SMALLER THAN CURB DIMENSION