

**R1-E.362-G10**

CFM	Static Pressure in Inches W.G.				
	0.000	0.250	0.500	0.750	1.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1200	905 / 0.11	1061 / 0.18	1263 / 0.30	1485 / 0.49	1697 / 0.73
1400	1055 / 0.18	1183 / 0.25	1344 / 0.36	1527 / 0.53	1716 / 0.76
1600	1206 / 0.26	1315 / 0.34	1445 / 0.45	1595 / 0.61	1758 / 0.81
1800	1356 / 0.37	1452 / 0.46	1561 / 0.57	1685 / 0.72	1824 / 0.91
2000	1507 / 0.51	1591 / 0.60	1686 / 0.72	1792 / 0.86	
2200	1658 / 0.68	1734 / 0.78	1817 / 0.90		
2400	1809 / 0.88	1876 / 0.99			

**Max Sizeable RPM = 1884 RPM. Table shown extended beyond this point for reference only.**

Motor BMN48-750I2-50-230/277 has an rpm range of 900 to 1800.

Motor BMN48-750I2-60-230/277 has an rpm range of 900 to 1800.

Motor M055PWCUK0315-ECM-50-115 has an rpm range of 900 to 1800.

Motor M055PWCUK0315-ECM-50-230 has an rpm range of 900 to 1800.

Motor M055PWCUK0315-ECM-60-115 has an rpm range of 900 to 1800.

Motor M055PWCUK0315-ECM-60-230 has an rpm range of 900 to 1800.