

R2-E.734-G15

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
3000	339 / 0.31	457 / 0.46	555 / 0.63	650 / 0.83	739 / 1.06	821 / 1.30	897 / 1.55	966 / 1.82	1031 / 2.10
3500	395 / 0.49	501 / 0.66	587 / 0.85	671 / 1.06	752 / 1.30	829 / 1.56	902 / 1.83	971 / 2.12	1036 / 2.42
4000	451 / 0.74	548 / 0.93	626 / 1.13	700 / 1.36	773 / 1.61	844 / 1.88	912 / 2.16	978 / 2.47	1041 / 2.78
4500	507 / 1.05	597 / 1.26	668 / 1.49	735 / 1.73	801 / 1.99	865 / 2.27	929 / 2.57	990 / 2.89	1050 / 3.22
5000	563 / 1.43	647 / 1.67	713 / 1.92	775 / 2.18	834 / 2.46	893 / 2.75	951 / 3.06	1009 / 3.39	1065 / 3.73
5500	620 / 1.91	698 / 2.17	760 / 2.44	817 / 2.72	872 / 3.01	927 / 3.32	980 / 3.65	1033 / 3.99	1085 / 4.34
6000	676 / 2.48	750 / 2.77	809 / 3.06	862 / 3.35	914 / 3.67	964 / 3.99	1013 / 4.33	1062 / 4.69	
6500	732 / 3.15	802 / 3.46	858 / 3.77	909 / 4.09	957 / 4.43	1004 / 4.77			

Max Sizeable RPM = 1200 RPM. Table shown extended beyond this point for reference only.