

R3-E.1224-G18

CFM	Static Pressure in Inches W.G.											
	0.000	0.200	0.400	0.600	0.800	1.000	1.200	1.400	1.600	1.800	2.000	
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4500	325 / 0.54	417 / 0.72	500 / 0.94	562 / 1.16	617 / 1.40	666 / 1.64	714 / 1.89	759 / 2.15	803 / 2.42	845 / 2.69		
5000	361 / 0.75	440 / 0.93	525 / 1.17	587 / 1.42	640 / 1.67	688 / 1.93	733 / 2.20	776 / 2.48	817 / 2.76	857 / 3.05	897 / 3.35	
5500	398 / 0.99	464 / 1.18	549 / 1.45	612 / 1.72	664 / 1.99	711 / 2.27	755 / 2.56	796 / 2.85	835 / 3.15	874 / 3.46	911 / 3.78	
6000	434 / 1.29	490 / 1.48	573 / 1.77	637 / 2.06	689 / 2.36	735 / 2.66	778 / 2.96	818 / 3.28	856 / 3.60	893 / 3.92	928 / 4.25	
6500	470 / 1.64	519 / 1.84	596 / 2.13	662 / 2.46	714 / 2.78	760 / 3.10	802 / 3.42	841 / 3.75	878 / 4.09	914 / 4.43	948 / 4.79	
7000	506 / 2.05	549 / 2.25	619 / 2.55	685 / 2.90	739 / 3.25	785 / 3.59	827 / 3.94	865 / 4.29	901 / 4.65	936 / 5.01	970 / 5.38	
7500	542 / 2.52	581 / 2.73	643 / 3.04	709 / 3.40	764 / 3.77	810 / 4.14	852 / 4.51	890 / 4.89	926 / 5.26	960 / 5.64	992 / 6.03	
8000	578 / 3.06	613 / 3.28	668 / 3.58	731 / 3.97	787 / 4.36	835 / 4.76	877 / 5.15	915 / 5.55	951 / 5.94	984 / 6.35	1016 / 6.75	

Max Sizeable RPM = 1100 RPM. Table shown extended beyond this point for reference only.