

R4-E.1684-920

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
9000	388 / 1.52	441 / 2.08	492 / 2.65	540 / 3.13	586 / 3.55	630 / 3.95	674 / 4.37	717 / 4.82	759 / 5.34
10000	431 / 2.08	479 / 2.69	526 / 3.35	570 / 3.93	613 / 4.43	654 / 4.89	693 / 5.33	733 / 5.79	772 / 6.28
11000	474 / 2.77	518 / 3.43	561 / 4.17	602 / 4.84	642 / 5.44	680 / 5.98	717 / 6.49	754 / 6.98	789 / 7.47
12000	517 / 3.60	557 / 4.30	597 / 5.11	636 / 5.88	673 / 6.58	709 / 7.21	743 / 7.79	778 / 8.34	811 / 8.88
13000	560 / 4.57	597 / 5.32	634 / 6.19	670 / 7.05	705 / 7.85	739 / 8.58	772 / 9.25	804 / 9.88	
14000	603 / 5.71	637 / 6.51	672 / 7.43	706 / 8.37	739 / 9.26				
15000	646 / 7.02	678 / 7.86	710 / 8.84	742 / 9.85					

Max Sizeable RPM = 1000 RPM. Table shown extended beyond this point for reference only.