

RARTU2-18

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
500		786 / 0.09	1094 / 0.21	1330 / 0.35	1529 / 0.51	1706 / 0.69	1866 / 0.88	2016 / 1.08	2155 / 1.30
750		815 / 0.12	1116 / 0.26	1351 / 0.43	1550 / 0.62	1724 / 0.81	1884 / 1.03	2033 / 1.26	2168 / 1.49
1000		864 / 0.15	1144 / 0.32	1376 / 0.51	1572 / 0.72	1745 / 0.94	1905 / 1.18	2049 / 1.43	2188 / 1.70
1250	650 / 0.04	934 / 0.19	1185 / 0.38	1404 / 0.59	1598 / 0.83	1771 / 1.08	1929 / 1.35	2073 / 1.62	2208 / 1.90
1500	780 / 0.07	1023 / 0.23	1243 / 0.44	1445 / 0.68	1630 / 0.94	1799 / 1.21	1953 / 1.50	2098 / 1.81	2232 / 2.12
1750	910 / 0.12	1123 / 0.30	1316 / 0.52	1500 / 0.77	1673 / 1.06	1834 / 1.35	1982 / 1.66	2126 / 2.00	2258 / 2.33
2000	1040 / 0.17	1229 / 0.37	1402 / 0.61	1567 / 0.88	1727 / 1.18	1876 / 1.49	2022 / 1.83	2160 / 2.19	2288 / 2.55
2250	1169 / 0.24	1341 / 0.47	1496 / 0.72	1646 / 1.01	1793 / 1.32	1933 / 1.66	2070 / 2.01	2202 / 2.39	2327 / 2.78
2500	1299 / 0.34	1456 / 0.58	1598 / 0.85	1735 / 1.15	1868 / 1.48	2000 / 1.84	2128 / 2.21	2250 / 2.60	2370 / 3.00
2750	1429 / 0.45	1573 / 0.71	1705 / 1.01	1831 / 1.32	1955 / 1.67	2075 / 2.04	2193 / 2.42	2307 / 2.82	2423 / 3.25
3000	1558 / 0.58	1693 / 0.87	1815 / 1.18	1932 / 1.52	2046 / 1.88	2158 / 2.26	2269 / 2.66	2377 / 3.08	2486 / 3.53

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 162778/A01-ECM-50-240-18 has an rpm range of 600 to 2700.

Motor 162778/A01-ECM-60-240-18 has an rpm range of 600 to 2700.

Motor 162779/A01-ECM-50-480-18 has an rpm range of 600 to 2700.

Motor 162779/A01-ECM-60-480-18 has an rpm range of 600 to 2700.