

RARTU2-E.604-18

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2500			964 / 0.70	1049 / 0.90	1129 / 1.13	1206 / 1.37	1279 / 1.62	1350 / 1.89	1418 / 2.17	1484 / 2.46	1548 / 2.77	1610 / 3.07	1670 / 3.39	1729 / 3.71	1787 / 4.04
2750		945 / 0.65	1027 / 0.85	1106 / 1.06	1181 / 1.29	1253 / 1.54	1323 / 1.81	1390 / 2.09	1455 / 2.38	1518 / 2.68	1580 / 3.00	1639 / 3.32	1696 / 3.65	1754 / 3.99	
3000	943 / 0.61	1017 / 0.81	1092 / 1.02	1166 / 1.24	1237 / 1.48	1305 / 1.74	1371 / 2.01	1435 / 2.30	1496 / 2.60	1557 / 2.92	1616 / 3.24	1672 / 3.58	1728 / 3.92	1783 / 4.27	

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Motor DHP00545 has an rpm range of 900 to 1750.

Motor DTP0054 has an rpm range of 900 to 1750.

Motor DTP0054-50 has an rpm range of 900 to 1435.

Motor EP00545 has an rpm range of 900 to 1745.

Motor GP0054 has an rpm range of 900 to 1800.

Motor GP0054-50 has an rpm range of 900 to 1440.