

RARTU2-I.100-18

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
750			1143 / 0.28	1374 / 0.45	1569 / 0.63	1744 / 0.84	1904 / 1.07	2049 / 1.30	2187 / 1.56
1000		926 / 0.18	1193 / 0.36	1414 / 0.54	1608 / 0.75	1779 / 0.98	1934 / 1.22	2079 / 1.48	2212 / 1.75
1250		1017 / 0.24	1259 / 0.45	1467 / 0.67	1653 / 0.90	1820 / 1.14	1972 / 1.40	2115 / 1.68	2248 / 1.97
1500		1124 / 0.31	1338 / 0.55	1532 / 0.81	1708 / 1.07	1870 / 1.34	2019 / 1.62	2155 / 1.91	2287 / 2.22
1750	1045 / 0.22	1241 / 0.40	1431 / 0.67	1610 / 0.96	1775 / 1.26	1927 / 1.56	2071 / 1.87	2207 / 2.19	2333 / 2.52
2000	1194 / 0.33	1366 / 0.51	1535 / 0.80	1698 / 1.13	1852 / 1.46	1996 / 1.80	2134 / 2.15	2262 / 2.49	2387 / 2.85
2250	1343 / 0.47	1496 / 0.66	1648 / 0.96	1796 / 1.31	1938 / 1.68	2074 / 2.06	2204 / 2.44	2329 / 2.83	2448 / 3.22
2500	1493 / 0.64	1630 / 0.84	1768 / 1.15	1903 / 1.52	2034 / 1.92	2161 / 2.33	2285 / 2.75	2404 / 3.18	2518 / 3.61
2750	1642 / 0.85	1766 / 1.06	1891 / 1.37	2016 / 1.76	2137 / 2.18	2256 / 2.62	2373 / 3.08	2484 / 3.54	2592 / 4.00
3000	1791 / 1.11	1905 / 1.32	2020 / 1.64	2135 / 2.03	2247 / 2.47	2358 / 2.94	2467 / 3.43	2573 / 3.92	2676 / 4.43

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 162778/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 162778/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 162779/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 162779/A01-ECM-60-480-18 has an rpm range of 900 to 2700.