

RARTU2-I.150-18

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000			1171 / 0.34	1397 / 0.53	1590 / 0.74	1764 / 0.97	1919 / 1.21	2066 / 1.46	2198 / 1.71
1250		979 / 0.21	1224 / 0.41	1438 / 0.63	1628 / 0.87	1796 / 1.12	1953 / 1.39	2094 / 1.66	2228 / 1.95
1500		1077 / 0.28	1294 / 0.50	1493 / 0.74	1672 / 1.00	1836 / 1.28	1989 / 1.58	2131 / 1.88	2262 / 2.19
1750	987 / 0.17	1186 / 0.36	1378 / 0.60	1558 / 0.86	1728 / 1.15	1886 / 1.46	2033 / 1.78	2169 / 2.10	2300 / 2.44
2000	1127 / 0.26	1303 / 0.47	1473 / 0.72	1637 / 1.01	1794 / 1.32	1942 / 1.64	2083 / 1.99	2215 / 2.34	2342 / 2.71
2250	1268 / 0.36	1425 / 0.60	1578 / 0.87	1727 / 1.18	1870 / 1.50	2009 / 1.85	2143 / 2.22	2270 / 2.60	2391 / 2.99
2500	1409 / 0.50	1551 / 0.76	1689 / 1.05	1825 / 1.37	1958 / 1.72	2087 / 2.09	2212 / 2.48	2332 / 2.87	2449 / 3.29
2750	1550 / 0.66	1679 / 0.94	1806 / 1.26	1930 / 1.60	2052 / 1.96	2172 / 2.35	2290 / 2.76	2404 / 3.18	2514 / 3.61
3000	1691 / 0.86	1809 / 1.17	1926 / 1.50	2041 / 1.86	2154 / 2.24	2266 / 2.65	2375 / 3.07	2483 / 3.52	2588 / 3.98

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 162778/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 162778/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 162779/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 162779/A01-ECM-60-480-18 has an rpm range of 900 to 2700.