

## RARTU2-I.200-18

| CFM     | Static Pressure in Inches W.G. |             |             |             |             |             |             |             |             |             |             |             |             |             |             |
|---------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
|         | 0.000                          | 0.250       | 0.500       | 0.750       | 1.000       | 1.250       | 1.500       | 1.750       | 2.000       | 2.250       | 2.500       | 2.750       | 3.000       | 3.250       | 3.500       |
| RPM/BHP | RPM/BHP                        | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     |
| 1500    |                                |             |             |             | 978 / 0.69  | 1075 / 0.88 | 1166 / 1.09 | 1252 / 1.30 | 1333 / 1.51 | 1411 / 1.74 | 1485 / 1.97 | 1554 / 2.20 | 1622 / 2.44 | 1687 / 2.68 | 1750 / 2.94 |
| 1750    |                                |             |             | 915 / 0.59  | 1012 / 0.79 | 1102 / 1.00 | 1188 / 1.22 | 1270 / 1.45 | 1348 / 1.69 | 1423 / 1.93 | 1494 / 2.18 | 1564 / 2.44 | 1629 / 2.69 | 1694 / 2.96 | 1755 / 3.22 |
| 2000    |                                |             |             | 962 / 0.69  | 1053 / 0.90 | 1138 / 1.12 | 1218 / 1.36 | 1295 / 1.60 | 1370 / 1.86 | 1441 / 2.12 | 1511 / 2.39 | 1577 / 2.67 | 1642 / 2.95 | 1704 / 3.23 | 1765 / 3.53 |
| 2250    |                                |             | 922 / 0.62  | 1014 / 0.81 | 1099 / 1.03 | 1179 / 1.26 | 1256 / 1.51 | 1328 / 1.77 | 1399 / 2.04 | 1467 / 2.32 | 1533 / 2.61 | 1597 / 2.91 | 1659 / 3.21 | 1720 / 3.52 | 1779 / 3.82 |
| 2500    |                                |             | 984 / 0.75  | 1069 / 0.96 | 1149 / 1.18 | 1225 / 1.43 | 1298 / 1.69 | 1368 / 1.96 | 1434 / 2.24 | 1499 / 2.54 | 1562 / 2.84 | 1623 / 3.15 | 1684 / 3.47 | 1741 / 3.79 | 1799 / 4.13 |
| 2750    |                                | 967 / 0.71  | 1048 / 0.91 | 1128 / 1.13 | 1204 / 1.36 | 1276 / 1.62 | 1345 / 1.89 | 1411 / 2.17 | 1475 / 2.46 | 1536 / 2.77 | 1597 / 3.09 | 1656 / 3.42 | 1712 / 3.75 | 1768 / 4.09 |             |
| 3000    | 971 / 0.68                     | 1041 / 0.88 | 1116 / 1.09 | 1190 / 1.32 | 1261 / 1.57 | 1329 / 1.83 | 1395 / 2.11 | 1458 / 2.41 | 1519 / 2.71 | 1579 / 3.03 | 1637 / 3.36 | 1692 / 3.69 | 1747 / 4.04 |             |             |

**Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.**

Motor DHP00545 has an rpm range of 900 to 1750.

Motor DTP0054 has an rpm range of 900 to 1750.

Motor DTP0054-50 has an rpm range of 900 to 1435.

Motor EP00545 has an rpm range of 900 to 1745.

Motor GP0054 has an rpm range of 900 to 1800.

Motor GP0054-50 has an rpm range of 900 to 1440.