

RARTU2-I.200HE-18

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500					991 / 0.72	1088 / 0.91	1177 / 1.12	1263 / 1.33	1344 / 1.55	1422 / 1.77	1496 / 2.00	1566 / 2.23	1632 / 2.46	1697 / 2.71	1758 / 2.95
1750				933 / 0.62	1029 / 0.82	1118 / 1.04	1204 / 1.26	1284 / 1.49	1362 / 1.73	1436 / 1.98	1507 / 2.23	1575 / 2.48	1642 / 2.74	1706 / 3.00	1768 / 3.27
2000				985 / 0.74	1074 / 0.95	1158 / 1.18	1238 / 1.42	1313 / 1.67	1387 / 1.93	1458 / 2.19	1526 / 2.46	1592 / 2.74	1656 / 3.02	1718 / 3.31	1779 / 3.60
2250			951 / 0.67	1041 / 0.88	1124 / 1.10	1203 / 1.34	1278 / 1.59	1351 / 1.86	1420 / 2.13	1487 / 2.41	1552 / 2.70	1615 / 3.00	1677 / 3.30	1737 / 3.61	1796 / 3.93
2500		928 / 0.63	1016 / 0.83	1100 / 1.04	1179 / 1.27	1254 / 1.52	1325 / 1.79	1394 / 2.07	1459 / 2.35	1523 / 2.65	1585 / 2.96	1646 / 3.28	1704 / 3.59	1762 / 3.92	
2750	928 / 0.60	1004 / 0.80	1085 / 1.01	1163 / 1.23	1237 / 1.48	1308 / 1.74	1376 / 2.01	1441 / 2.30	1504 / 2.60	1565 / 2.92	1624 / 3.24	1682 / 3.57	1738 / 3.91	1792 / 4.24	
3000	1012 / 0.78	1082 / 1.00	1155 / 1.22	1228 / 1.46	1298 / 1.71	1365 / 1.98	1430 / 2.27	1493 / 2.57	1553 / 2.88	1611 / 3.21	1668 / 3.54	1723 / 3.89	1777 / 4.24		

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Motor DHP00545 has an rpm range of 900 to 1750.

Motor DTP0054 has an rpm range of 900 to 1750.

Motor DTP0054-50 has an rpm range of 900 to 1435.

Motor EP00545 has an rpm range of 900 to 1745.

Motor GP0054 has an rpm range of 900 to 1800.

Motor GP0054-50 has an rpm range of 900 to 1440.