

RARTU2-I.50HE-18

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
500			1134 / 0.23	1366 / 0.38	1562 / 0.54	1742 / 0.73	1901 / 0.93	2041 / 1.12	2183 / 1.35
750		933 / 0.17	1202 / 0.32	1423 / 0.49	1613 / 0.68	1786 / 0.89	1943 / 1.12	2083 / 1.34	2219 / 1.59
1000		1050 / 0.25	1294 / 0.44	1499 / 0.64	1681 / 0.86	1845 / 1.09	1996 / 1.33	2137 / 1.59	2268 / 1.86
1250	931 / 0.18	1185 / 0.38	1404 / 0.59	1594 / 0.82	1766 / 1.07	1920 / 1.33	2066 / 1.60	2201 / 1.88	2328 / 2.18
1500	1118 / 0.32	1332 / 0.54	1529 / 0.79	1705 / 1.06	1866 / 1.34	2013 / 1.62	2149 / 1.92	2280 / 2.23	2404 / 2.56
1750	1304 / 0.50	1489 / 0.76	1665 / 1.04	1829 / 1.35	1977 / 1.65	2116 / 1.97	2246 / 2.30	2368 / 2.63	2489 / 2.99
2000	1490 / 0.75	1653 / 1.04	1810 / 1.35	1961 / 1.69	2101 / 2.04	2232 / 2.39	2356 / 2.75	2475 / 3.13	2587 / 3.50
2250	1677 / 1.06	1820 / 1.38	1963 / 1.74	2101 / 2.10	2232 / 2.49	2356 / 2.88	2473 / 3.27	2586 / 3.68	2695 / 4.09
2500	1863 / 1.46	1992 / 1.81	2122 / 2.20	2248 / 2.60	2370 / 3.01	2485 / 3.43	2599 / 3.87		
2750	2049 / 1.94	2167 / 2.33	2284 / 2.74	2402 / 3.18	2514 / 3.62	2624 / 4.08			
3000	2235 / 2.52	2342 / 2.93	2451 / 3.38	2560 / 3.85	2664 / 4.33				

Max Sizeable RPM = 2700 RPM. Table shown extended beyond this point for reference only.

Motor 162778/A01-ECM-50-240-18 has an rpm range of 900 to 2700.

Motor 162778/A01-ECM-60-240-18 has an rpm range of 900 to 2700.

Motor 162779/A01-ECM-50-480-18 has an rpm range of 900 to 2700.

Motor 162779/A01-ECM-60-480-18 has an rpm range of 900 to 2700.