

RARTU3-22

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000		621 / 0.15	861 / 0.35	1046 / 0.58	1203 / 0.83	1342 / 1.11	1468 / 1.40	1582 / 1.71	1692 / 2.05
1500		655 / 0.20	882 / 0.45	1065 / 0.73	1221 / 1.03	1357 / 1.35	1482 / 1.69	1597 / 2.04	1705 / 2.42
2000		717 / 0.27	915 / 0.55	1089 / 0.87	1241 / 1.23	1377 / 1.60	1502 / 1.98	1616 / 2.39	1721 / 2.81
2500	616 / 0.11	801 / 0.36	969 / 0.67	1126 / 1.03	1270 / 1.43	1401 / 1.84	1523 / 2.28	1635 / 2.73	1741 / 3.20
3000	739 / 0.18	898 / 0.47	1041 / 0.82	1179 / 1.21	1310 / 1.64	1434 / 2.10	1550 / 2.58	1660 / 3.08	1764 / 3.60
3500	861 / 0.29	1002 / 0.62	1127 / 1.00	1248 / 1.42	1366 / 1.88	1479 / 2.37	1589 / 2.89	1693 / 3.44	1792 / 4.00
4000	984 / 0.43	1110 / 0.81	1222 / 1.22	1329 / 1.67	1435 / 2.16	1538 / 2.68	1639 / 3.23	1736 / 3.81	1831 / 4.42
4500	1108 / 0.61	1221 / 1.03	1322 / 1.48	1419 / 1.96	1515 / 2.48	1607 / 3.03	1700 / 3.62	1791 / 4.23	1879 / 4.87
5000	1230 / 0.84	1334 / 1.30	1427 / 1.79	1516 / 2.31	1603 / 2.86	1688 / 3.44	1772 / 4.05	1855 / 4.69	
5500	1353 / 1.12	1449 / 1.63	1535 / 2.16	1617 / 2.71	1697 / 3.29	1775 / 3.90	1853 / 4.55		
6000	1476 / 1.45	1565 / 2.01	1645 / 2.58	1722 / 3.17	1796 / 3.79	1869 / 4.43			

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 500 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 500 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 500 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 500 to 1900.