

RARTU3-E.1002-24

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4500		839 / 1.53	965 / 2.29	1077 / 3.16	1180 / 4.12	1276 / 5.14	1366 / 6.21	1452 / 7.33	1533 / 8.49
4750	725 / 0.97	870 / 1.72	992 / 2.50	1101 / 3.39	1202 / 4.37	1295 / 5.42	1384 / 6.53	1468 / 7.68	1548 / 8.86
5000	763 / 1.14	903 / 1.92	1021 / 2.73	1127 / 3.64	1225 / 4.64	1316 / 5.71	1403 / 6.85	1485 / 8.03	1564 / 9.26
5250	801 / 1.32	935 / 2.14	1050 / 2.98	1153 / 3.90	1249 / 4.93	1338 / 6.03	1423 / 7.19	1503 / 8.40	1581 / 9.66
5500	839 / 1.51	968 / 2.39	1080 / 3.24	1180 / 4.19	1273 / 5.23	1361 / 6.36	1444 / 7.54	1523 / 8.79	
5750	878 / 1.73	1002 / 2.65	1110 / 3.54	1208 / 4.50	1299 / 5.56	1384 / 6.71	1465 / 7.92	1543 / 9.19	
6000	916 / 1.96	1035 / 2.93	1141 / 3.85	1236 / 4.84	1325 / 5.92	1408 / 7.08	1488 / 8.31	1565 / 9.61	

Max Sizeable RPM = 1600 RPM. Table shown extended beyond this point for reference only.

Motor DHP01045 has an rpm range of 700 to 1600.

Motor DTP0104 has an rpm range of 700 to 1600.

Motor DTP0104-50 has an rpm range of 700 to 1600.

Motor EP01045 has an rpm range of 700 to 1600.

Motor GP0104 has an rpm range of 700 to 1600.

Motor GP0104-50 has an rpm range of 700 to 1440.