

RARTU3-E.1004-22

CFM	Static Pressure in Inches W.G.														
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4500	1181 / 0.88	1236 / 1.09	1287 / 1.31	1337 / 1.54	1385 / 1.78	1432 / 2.02	1479 / 2.28	1526 / 2.55	1573 / 2.82	1619 / 3.11	1665 / 3.40	1711 / 3.70	1756 / 4.00	1801 / 4.32	1846 / 4.64
4750	1246 / 1.03	1299 / 1.26	1348 / 1.49	1395 / 1.73	1441 / 1.97	1486 / 2.23	1531 / 2.50	1575 / 2.77	1620 / 3.05	1664 / 3.34	1708 / 3.65	1751 / 3.95	1794 / 4.26	1838 / 4.58	1880 / 4.91
5000	1312 / 1.21	1362 / 1.44	1409 / 1.68	1454 / 1.93	1498 / 2.19	1541 / 2.45	1584 / 2.73	1627 / 3.01	1669 / 3.30	1711 / 3.60	1753 / 3.91	1794 / 4.22	1836 / 4.55	1877 / 4.88	
5250	1378 / 1.40	1425 / 1.64	1470 / 1.89	1514 / 2.15	1556 / 2.42	1597 / 2.70	1639 / 2.98	1679 / 3.27	1720 / 3.57	1759 / 3.88	1800 / 4.20	1840 / 4.52	1879 / 4.85		
5500	1443 / 1.60	1489 / 1.86	1532 / 2.12	1574 / 2.39	1614 / 2.67	1654 / 2.96	1693 / 3.25	1732 / 3.55	1771 / 3.86	1810 / 4.18	1848 / 4.50	1886 / 4.83			
5750	1509 / 1.83	1553 / 2.10	1594 / 2.38	1634 / 2.66	1673 / 2.94	1712 / 3.24	1750 / 3.54	1787 / 3.85	1824 / 4.17	1861 / 4.50	1898 / 4.83				
6000	1574 / 2.08	1616 / 2.36	1657 / 2.65	1695 / 2.94	1733 / 3.24	1770 / 3.54	1807 / 3.86	1843 / 4.18	1879 / 4.50						

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 800 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 800 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 800 to 1900.