

RARTU3-E.152-18

CFM	Static Pressure in Inches W.G.															
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250	2.500	2.750	3.000	3.250	3.500	3.750
RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000					936 / 0.51	1043 / 0.66	1139 / 0.83	1227 / 1.00	1311 / 1.18	1387 / 1.36	1460 / 1.56	1529 / 1.76	1595 / 1.97	1658 / 2.19	1718 / 2.41	1776 / 2.64
1500					968 / 0.67	1067 / 0.86	1159 / 1.07	1246 / 1.28	1327 / 1.50	1404 / 1.72	1478 / 1.95	1546 / 2.18	1613 / 2.42	1678 / 2.67	1738 / 2.91	1799 / 3.17
2000				941 / 0.65	1033 / 0.85	1120 / 1.07	1203 / 1.31	1282 / 1.55	1358 / 1.81	1431 / 2.07	1500 / 2.34	1569 / 2.62	1633 / 2.90	1696 / 3.19	1756 / 3.48	
2500			962 / 0.70	1044 / 0.89	1124 / 1.11	1200 / 1.35	1273 / 1.60	1343 / 1.87	1412 / 2.15	1479 / 2.44	1543 / 2.74	1607 / 3.06	1668 / 3.38	1727 / 3.70	1784 / 4.03	
3000	938 / 0.60	1017 / 0.81	1091 / 1.01	1163 / 1.23	1232 / 1.46	1299 / 1.72	1364 / 1.98	1427 / 2.27	1489 / 2.57	1549 / 2.88	1608 / 3.20	1665 / 3.53	1722 / 3.88	1777 / 4.24		
3500	1095 / 0.95	1162 / 1.20	1227 / 1.43	1290 / 1.68	1351 / 1.93	1411 / 2.20	1469 / 2.49	1526 / 2.78	1582 / 3.10	1636 / 3.42	1690 / 3.76	1742 / 4.11	1794 / 4.47			
4000	1251 / 1.42	1310 / 1.70	1368 / 1.97	1424 / 2.25	1479 / 2.53	1533 / 2.82	1585 / 3.12	1637 / 3.44	1687 / 3.76	1737 / 4.10	1786 / 4.46					
4500	1407 / 2.02	1460 / 2.34	1511 / 2.64	1562 / 2.95	1612 / 3.27	1661 / 3.58	1708 / 3.90	1756 / 4.24								
5000	1563 / 2.77	1611 / 3.13	1658 / 3.47	1704 / 3.81	1749 / 4.15	1794 / 4.50										
5500	1720 / 3.69	1763 / 4.08														

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

- Motor DHP00545 has an rpm range of 900 to 1750.
- Motor DTP0054 has an rpm range of 900 to 1750.
- Motor DTP0054-50 has an rpm range of 900 to 1435.
- Motor EP00545 has an rpm range of 900 to 1745.
- Motor GP0054 has an rpm range of 900 to 1800.
- Motor GP0054-50 has an rpm range of 900 to 1440.