

RARTU3-E.304-18

CFM	Static Pressure in Inches W.G.							
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			968 / 0.67	1159 / 1.07	1327 / 1.50	1478 / 1.95	1613 / 2.42	1738 / 2.91
2000			1033 / 0.85	1203 / 1.31	1358 / 1.81	1500 / 2.34	1633 / 2.90	1756 / 3.48
2500		962 / 0.70	1124 / 1.11	1273 / 1.60	1412 / 2.15	1543 / 2.74	1668 / 3.38	1784 / 4.03
3000	938 / 0.60	1091 / 1.01	1232 / 1.46	1364 / 1.98	1489 / 2.57	1608 / 3.20	1722 / 3.88	
3500	1095 / 0.95	1227 / 1.43	1351 / 1.93	1469 / 2.49	1582 / 3.10	1690 / 3.76	1794 / 4.47	
4000	1251 / 1.42	1368 / 1.97	1479 / 2.53	1585 / 3.12	1687 / 3.76	1786 / 4.46		
4500	1407 / 2.02	1511 / 2.64	1612 / 3.27	1708 / 3.90				
5000	1563 / 2.77	1658 / 3.47	1749 / 4.15					
5500	1720 / 3.69							

Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.

Motor DHP00545 has an rpm range of 900 to 1750.

Motor DTP0054 has an rpm range of 900 to 1750.

Motor DTP0054-50 has an rpm range of 900 to 1435.

Motor EP00545 has an rpm range of 900 to 1745.

Motor GP0054 has an rpm range of 900 to 1800.

Motor GP0054-50 has an rpm range of 900 to 1440.