

RARTU3-E.452-15

CFM	Static Pressure in Inches W.G.									
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000	2.250
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000	971 / 0.27	1107 / 0.42	1197 / 0.56	1280 / 0.71	1361 / 0.86	1443 / 1.03	1526 / 1.22	1606 / 1.41	1689 / 1.63	1771 / 1.85
2250	1092 / 0.38	1221 / 0.56	1306 / 0.71	1381 / 0.87	1454 / 1.04	1527 / 1.22	1599 / 1.41	1673 / 1.61	1746 / 1.82	
2500	1214 / 0.52	1337 / 0.72	1416 / 0.90	1487 / 1.07	1555 / 1.25	1620 / 1.44	1686 / 1.64	1751 / 1.84		
2750	1335 / 0.69	1453 / 0.92	1529 / 1.11	1596 / 1.30	1659 / 1.50	1720 / 1.70	1780 / 1.91			
3000	1456 / 0.90	1571 / 1.16	1644 / 1.37	1707 / 1.57	1767 / 1.78	1824 / 2.00				
3250	1578 / 1.15	1687 / 1.43	1759 / 1.66	1820 / 1.88						
3500	1699 / 1.43	1805 / 1.74	1875 / 1.99							
3750	1820 / 1.76									

Max Sizeable RPM = 2200 RPM. Table shown extended beyond this point for reference only.

Motor DHP00245 has an rpm range of 900 to 1745.

Motor DTP0024 has an rpm range of 900 to 1740.

Motor DTP0024-50HZ has an rpm range of 900 to 1415.

Motor EP00245 has an rpm range of 900 to 1800.

Motor GP0024 has an rpm range of 900 to 1800.

Motor GP0024-50 has an rpm range of 900 to 1440.