

RARTU3-E.606-22

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2500		834 / 0.41	1000 / 0.74	1156 / 1.11	1299 / 1.51	1431 / 1.94	1552 / 2.39	1664 / 2.85	1769 / 3.33
3000		939 / 0.56	1080 / 0.92	1216 / 1.33	1346 / 1.77	1471 / 2.24	1586 / 2.73	1696 / 3.25	1800 / 3.78
3500	919 / 0.41	1051 / 0.76	1173 / 1.15	1292 / 1.59	1409 / 2.07	1522 / 2.57	1631 / 3.11	1735 / 3.67	1835 / 4.25
4000	1050 / 0.62	1168 / 1.00	1276 / 1.43	1381 / 1.90	1485 / 2.41	1587 / 2.95	1687 / 3.53	1785 / 4.13	1879 / 4.74
4500	1181 / 0.88	1287 / 1.31	1385 / 1.78	1479 / 2.28	1573 / 2.82	1665 / 3.40	1756 / 4.00	1846 / 4.64	
5000	1312 / 1.21	1409 / 1.68	1498 / 2.19	1584 / 2.73	1669 / 3.30	1753 / 3.91	1836 / 4.55		
5500	1443 / 1.60	1532 / 2.12	1614 / 2.67	1693 / 3.25	1771 / 3.86	1848 / 4.50			
6000	1574 / 2.08	1657 / 2.65	1733 / 3.24	1807 / 3.86	1879 / 4.50				

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 800 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 800 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 800 to 1900.