

RARTU3-E.902-22

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4000	1050 / 0.62	1168 / 1.00	1276 / 1.43	1381 / 1.90	1485 / 2.41	1587 / 2.95	1687 / 3.53	1785 / 4.13	1879 / 4.74
4250	1115 / 0.74	1227 / 1.15	1330 / 1.60	1430 / 2.08	1528 / 2.61	1625 / 3.17	1721 / 3.76	1813 / 4.37	
4500	1181 / 0.88	1287 / 1.31	1385 / 1.78	1479 / 2.28	1573 / 2.82	1665 / 3.40	1756 / 4.00	1846 / 4.64	
4750	1246 / 1.03	1348 / 1.49	1441 / 1.97	1531 / 2.50	1620 / 3.05	1708 / 3.65	1794 / 4.26	1880 / 4.91	
5000	1312 / 1.21	1409 / 1.68	1498 / 2.19	1584 / 2.73	1669 / 3.30	1753 / 3.91	1836 / 4.55		
5250	1378 / 1.40	1470 / 1.89	1556 / 2.42	1639 / 2.98	1720 / 3.57	1800 / 4.20	1879 / 4.85		
5500	1443 / 1.60	1532 / 2.12	1614 / 2.67	1693 / 3.25	1771 / 3.86	1848 / 4.50			
5750	1509 / 1.83	1594 / 2.38	1673 / 2.94	1750 / 3.54	1824 / 4.17	1898 / 4.83			
6000	1574 / 2.08	1657 / 2.65	1733 / 3.24	1807 / 3.86	1879 / 4.50				

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 800 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 800 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 800 to 1900.