

RARTU3-E.906-15

CFM	Static Pressure in Inches W.G.						
	0.000	0.100	0.200	0.300	0.400	0.500	0.600
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
4000	1942 / 2.14	1989 / 2.30	2025 / 2.44	2055 / 2.56	2083 / 2.69	2107 / 2.80	2131 / 2.92
4100	1990 / 2.30	2037 / 2.47	2073 / 2.61	2104 / 2.75	2130 / 2.87	2154 / 2.99	
4200	2039 / 2.47	2084 / 2.64	2120 / 2.79	2151 / 2.93			
4300	2087 / 2.66	2133 / 2.83	2168 / 2.99				
4400	2136 / 2.85						

Max Sizeable RPM = 2200 RPM. Table shown extended beyond this point for reference only.

Motor DHP00245 has an rpm range of 900 to 1745.

Motor DTP0024 has an rpm range of 900 to 1740.

Motor DTP0024-50HZ has an rpm range of 900 to 1415.

Motor DTP0032 has an rpm range of 900 to 2200.

Motor EP00245 has an rpm range of 900 to 1800.

Motor GP0024 has an rpm range of 900 to 1800.

Motor GP0024-50 has an rpm range of 900 to 1440.