

RARTU3-I.150HE-22

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1000			901 / 0.40	1082 / 0.64	1238 / 0.90	1376 / 1.19	1502 / 1.50	1618 / 1.83	1727 / 2.17
1500			963 / 0.56	1135 / 0.85	1283 / 1.17	1416 / 1.51	1538 / 1.87	1650 / 2.24	1756 / 2.64
2000		860 / 0.47	1044 / 0.78	1204 / 1.13	1346 / 1.50	1473 / 1.88	1591 / 2.30	1699 / 2.72	1802 / 3.16
2500	826 / 0.39	985 / 0.71	1143 / 1.08	1288 / 1.48	1420 / 1.90	1542 / 2.35	1655 / 2.80	1761 / 3.28	1860 / 3.78
3000	991 / 0.68	1123 / 1.04	1257 / 1.46	1387 / 1.92	1508 / 2.40	1622 / 2.90	1730 / 3.41	1830 / 3.94	
3500	1155 / 1.07	1268 / 1.49	1384 / 1.96	1498 / 2.47	1608 / 3.00	1715 / 3.56	1815 / 4.13		
4000	1321 / 1.60	1419 / 2.08	1520 / 2.59	1621 / 3.15	1720 / 3.73	1817 / 4.34			
4500	1485 / 2.28	1572 / 2.81	1662 / 3.37	1752 / 3.98	1842 / 4.62				
5000	1651 / 3.13	1729 / 3.71	1808 / 4.32	1890 / 4.98					

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 800 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 800 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 800 to 1900.