

## RARTU3-I.200-18

| CFM  | Static Pressure in Inches W.G. |             |             |             |             |             |             |             |             |             |             |             |             |             |             |
|------|--------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
|      | 0.000                          | 0.250       | 0.500       | 0.750       | 1.000       | 1.250       | 1.500       | 1.750       | 2.000       | 2.250       | 2.500       | 2.750       | 3.000       | 3.250       | 3.500       |
|      | RPM/BHP                        | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     | RPM/BHP     |
| 1500 |                                |             |             |             | 985 / 0.70  | 1082 / 0.90 | 1174 / 1.11 | 1259 / 1.32 | 1340 / 1.53 | 1416 / 1.75 | 1490 / 1.98 | 1559 / 2.21 | 1625 / 2.44 | 1689 / 2.68 | 1750 / 2.93 |
| 2000 |                                |             |             | 969 / 0.71  | 1060 / 0.92 | 1145 / 1.14 | 1227 / 1.38 | 1305 / 1.64 | 1379 / 1.90 | 1451 / 2.16 | 1521 / 2.44 | 1587 / 2.72 | 1652 / 3.00 | 1714 / 3.28 | 1775 / 3.58 |
| 2500 |                                | 916 / 0.61  | 1001 / 0.79 | 1082 / 0.99 | 1160 / 1.21 | 1235 / 1.46 | 1307 / 1.72 | 1377 / 2.00 | 1444 / 2.29 | 1510 / 2.59 | 1573 / 2.90 | 1635 / 3.22 | 1695 / 3.54 | 1753 / 3.87 |             |
| 3000 | 994 / 0.74                     | 1067 / 0.95 | 1139 / 1.17 | 1210 / 1.39 | 1278 / 1.63 | 1343 / 1.89 | 1408 / 2.17 | 1470 / 2.46 | 1531 / 2.77 | 1590 / 3.09 | 1647 / 3.42 | 1705 / 3.77 | 1760 / 4.12 |             |             |
| 3500 | 1159 / 1.17                    | 1222 / 1.42 | 1284 / 1.67 | 1346 / 1.93 | 1406 / 2.19 | 1465 / 2.47 | 1522 / 2.76 | 1578 / 3.06 | 1633 / 3.39 | 1687 / 3.72 | 1740 / 4.07 | 1791 / 4.43 |             |             |             |
| 4000 | 1325 / 1.74                    | 1380 / 2.04 | 1435 / 2.32 | 1489 / 2.61 | 1543 / 2.90 | 1596 / 3.20 | 1647 / 3.51 | 1698 / 3.83 | 1747 / 4.17 | 1797 / 4.52 |             |             |             |             |             |
| 4500 | 1491 / 2.48                    | 1539 / 2.81 | 1588 / 3.14 | 1637 / 3.46 | 1685 / 3.78 | 1732 / 4.10 | 1779 / 4.44 |             |             |             |             |             |             |             |             |
| 5000 | 1656 / 3.41                    | 1700 / 3.77 | 1744 / 4.13 | 1788 / 4.49 |             |             |             |             |             |             |             |             |             |             |             |

**Max Sizeable RPM = 1800 RPM. Table shown extended beyond this point for reference only.**

Motor DHP00545 has an rpm range of 900 to 1750.

Motor DTP0054 has an rpm range of 900 to 1750.

Motor DTP0054-50 has an rpm range of 900 to 1435.

Motor EP00545 has an rpm range of 900 to 1745.

Motor GP0054 has an rpm range of 900 to 1800.

Motor GP0054-50 has an rpm range of 900 to 1440.