

RARTU3-I.200-22

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			916 / 0.49	1096 / 0.78	1249 / 1.09	1385 / 1.42	1509 / 1.77	1623 / 2.14	1730 / 2.53
2000			968 / 0.64	1137 / 0.98	1286 / 1.34	1419 / 1.72	1541 / 2.12	1654 / 2.54	1759 / 2.97
2500		874 / 0.48	1038 / 0.82	1191 / 1.20	1332 / 1.61	1460 / 2.04	1579 / 2.49	1690 / 2.96	1793 / 3.44
3000	845 / 0.36	987 / 0.68	1126 / 1.05	1261 / 1.47	1390 / 1.93	1511 / 2.41	1625 / 2.91	1732 / 3.43	1833 / 3.95
3500	985 / 0.57	1108 / 0.93	1228 / 1.35	1346 / 1.80	1462 / 2.30	1573 / 2.82	1680 / 3.37	1782 / 3.93	1880 / 4.52
4000	1126 / 0.85	1234 / 1.26	1340 / 1.71	1444 / 2.21	1547 / 2.74	1648 / 3.30	1747 / 3.89	1842 / 4.50	
4500	1267 / 1.21	1363 / 1.66	1457 / 2.16	1551 / 2.69	1644 / 3.26	1735 / 3.86	1825 / 4.49		
5000	1407 / 1.66	1494 / 2.16	1580 / 2.70	1664 / 3.27	1748 / 3.87	1831 / 4.51			
5500	1548 / 2.22	1628 / 2.76	1705 / 3.34	1782 / 3.94	1859 / 4.59				
6000	1689 / 2.88	1762 / 3.46	1833 / 4.08						

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 800 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 800 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 800 to 1900.