

RARTU3-I.200-22

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1500			925 / 0.51	1103 / 0.79	1255 / 1.10	1391 / 1.44	1515 / 1.79	1629 / 2.16	1736 / 2.55
2000			982 / 0.67	1149 / 1.00	1297 / 1.36	1430 / 1.75	1550 / 2.15	1663 / 2.57	1767 / 3.00
2500		894 / 0.52	1058 / 0.87	1209 / 1.25	1348 / 1.66	1476 / 2.10	1593 / 2.55	1703 / 3.02	1805 / 3.50
3000	872 / 0.41	1012 / 0.74	1150 / 1.13	1284 / 1.55	1412 / 2.01	1532 / 2.50	1644 / 3.00	1749 / 3.51	1851 / 4.06
3500	1018 / 0.66	1137 / 1.03	1257 / 1.45	1375 / 1.92	1489 / 2.42	1600 / 2.95	1706 / 3.51	1806 / 4.07	
4000	1163 / 0.98	1267 / 1.40	1372 / 1.86	1477 / 2.37	1579 / 2.91	1680 / 3.49	1778 / 4.08	1873 / 4.70	
4500	1308 / 1.39	1401 / 1.86	1495 / 2.37	1587 / 2.91	1680 / 3.50	1771 / 4.11	1861 / 4.75		
5000	1453 / 1.91	1538 / 2.42	1621 / 2.97	1705 / 3.56	1788 / 4.18	1871 / 4.84			
5500	1599 / 2.55	1675 / 3.10	1751 / 3.70	1827 / 4.33					
6000	1744 / 3.31	1814 / 3.91	1884 / 4.55						

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 800 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 800 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 800 to 1900.