

RARTU3-I.300-22

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2000			942 / 0.60	1115 / 0.93	1267 / 1.29	1402 / 1.66	1524 / 2.06	1638 / 2.47	1745 / 2.91
2500		838 / 0.42	1002 / 0.74	1158 / 1.12	1302 / 1.52	1433 / 1.95	1554 / 2.39	1667 / 2.86	1772 / 3.34
3000		943 / 0.57	1083 / 0.93	1219 / 1.34	1350 / 1.78	1473 / 2.25	1589 / 2.75	1699 / 3.26	1802 / 3.79
3500	923 / 0.43	1055 / 0.77	1177 / 1.16	1296 / 1.60	1412 / 2.08	1526 / 2.59	1635 / 3.13	1739 / 3.69	1838 / 4.27
4000	1055 / 0.63	1173 / 1.02	1278 / 1.44	1386 / 1.93	1490 / 2.44	1592 / 2.98	1691 / 3.55	1789 / 4.15	1883 / 4.77
4500	1187 / 0.90	1293 / 1.33	1391 / 1.80	1485 / 2.31	1578 / 2.85	1670 / 3.43	1761 / 4.04	1851 / 4.68	
5000	1319 / 1.24	1415 / 1.71	1504 / 2.22	1590 / 2.77	1675 / 3.35	1759 / 3.96	1842 / 4.59		
5500	1451 / 1.65	1539 / 2.17	1621 / 2.72	1700 / 3.30	1778 / 3.92	1854 / 4.56			
6000	1583 / 2.14	1664 / 2.70	1741 / 3.30	1814 / 3.92	1886 / 4.57				

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 800 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 800 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 800 to 1900.