

RARTU3-I.400HE-22

CFM	Static Pressure in Inches W.G.								
	0.000	0.500	1.000	1.500	2.000	2.500	3.000	3.500	4.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
2500		885 / 0.51	1049 / 0.85	1201 / 1.23	1341 / 1.64	1469 / 2.07	1587 / 2.53	1697 / 2.99	1800 / 3.48
3000	860 / 0.39	1001 / 0.71	1140 / 1.09	1274 / 1.52	1402 / 1.97	1522 / 2.45	1636 / 2.96	1742 / 3.48	1843 / 4.01
3500	1004 / 0.62	1125 / 0.99	1244 / 1.41	1362 / 1.87	1477 / 2.37	1588 / 2.89	1694 / 3.44	1796 / 4.01	1893 / 4.60
4000	1147 / 0.92	1253 / 1.34	1358 / 1.80	1463 / 2.30	1564 / 2.83	1666 / 3.40	1764 / 4.00	1860 / 4.62	
4500	1290 / 1.32	1385 / 1.77	1478 / 2.27	1571 / 2.81	1664 / 3.39	1755 / 4.00	1845 / 4.63		
5000	1433 / 1.80	1519 / 2.31	1603 / 2.85	1687 / 3.43	1771 / 4.05	1854 / 4.70			
5500	1577 / 2.40	1655 / 2.95	1731 / 3.54	1808 / 4.16	1884 / 4.82				
6000	1720 / 3.12	1792 / 3.71	1862 / 4.34						

Max Sizeable RPM = 1900 RPM. Table shown extended beyond this point for reference only.

Motor 163902/A01-ECM-50-240-22 has an rpm range of 800 to 1870.

Motor 163902/A01-ECM-60-240-22 has an rpm range of 800 to 1870.

Motor 163903/A01-ECM-50-480-22 has an rpm range of 800 to 1900.

Motor 163903/A01-ECM-60-480-22 has an rpm range of 800 to 1900.